Cosmos XP-3360 Handheld Combustible PPM Gas Detector



The portable Cosmos XP-3360 provides gas detection for environmental safety and spot check applications. When the target is set to Isobutane, Methane or Propane, a single unit can detect PPM levels of up to 32 combustible gases.

Simplified operation and a large digital display allow you to easily view gas threshold and concentration levels. This lightweight and compact detector features a rugged construction. Built to endure the elements, it is tested to withstand water pressure equivalent to over 16' of submersion and falls up to 23'.













Specifications

Model		XP-3360II
Target Gas		Combustible gas / solvent vapor
Detection Principle		Catalytic
Measure Range (Reference Indication)		0-5000ppm or 0-10000ppm (5001-5500ppm or 10001-11000ppm)
Accuracy*2		≤10%F.S.: ±1 %F.S. >10%F.S.: ±5 %F.S.
Resolution		1ppm
Alarm Set Value		250ppm or 500ppm
Response Time		T90: 30 seconds
Continuous Operation Time*3		Approx. 15 hours
Sampling Method		Extractive
Alarm Method	Gas Alarm	Beeping with flashing red light and AL icon on the LCD
	Device Error	Beeping with flashing yellow light and error message on the LCD
Power Source		•Non-rechargeable alkaline AA battery x4: Toshiba LR6, Panasonic LR6X, Duracell MN1500, Energizer E91 or Varta 4106
		·Rechargeable nickel metal hydride AA battery x4: New Cosmos HR-3UTG
Operating Temperature/Humidity		-20 to +50°C 95%RH. No condensation
Compliance*1		ATEX: Ex II 1G Ex ia da IIC T4 Ga *1
		IECEx: Ex ia da IIC T4 Ga *1
		CE (ATEX, RoHS and RE directives)
Ingress Protection		IP67
Main Features		Self-diagnosis (sensor error), Zero adjustment, Battery level indication, Flashlight, Peak-hold, LCD backlight, Audio alarm muting during gas alarm, Time indication, Alarm test, Alarm volume change, Audio muting
Dimensions		3.58"W x 6.45"H x 1.73"D (W91 x H164 x D44mm)
Weight		Approx. 1 lb. (460g), including batteries
Accessories		Gas sampling tube(1m), Shoulder strap, Drain filter, Filter element, Alkaline AA batteries (or Rechargeable nickel metal hydride AA batteries) x 4, Screen protector film x 3

 $^{^{\}star 1}$ When using alkaline AA batteries. Please contact us for full information.

^{*2} Under an identical measurement condition.

 $^{^{*3}}$ At 25 $^{\circ}$ C, with no alarm and backlight off. The time varies according to the circumstances, condition of use, storage period, battery manufacturer, etc.



DETECTOR DETAIL

Shoulder Strap Portable Gas Detector
XP-3000II Series
Instruction Manual
This will all the properties of the first series required in the first se

Instruction Manual

Akaline AA Batteries

Filter Element

> Gas Sampling Wand and Tube

Inspection Certificate





REALIBILITY & SUPPORT

DOD Technologies is the global leader in low level gas detection systems and solutions. We understand the importance of keeping your business operational and know that that false alarms can cost millions of dollars in lost productivity.

In addition to our ChemLogic® systems, we've partnered with other leading manufacturers to establish a comprehensive line of high-quality, gas detection products. Our worldwide network of knowledgeable service engineers are also stand ready to assist you with their passion for gas detection. Our portfolio includes fixed systems, portable gas detectors, controllers, systems integration and on-site field services.

For more information, or to order, please visit us at <u>DODtec.com</u>.



<u>Distributed by</u>: DOD Technologies, Inc. 675 Industrial Drive Cary, IL 60013



(815) 788-5200



solutions@dodtec.com



DODtec.com